

Window & Door Installation

Ensure a Proper Install Every Time



JELD-WEN recommends the OSI° QUAD° Installation System for installing our windows and doors.

SIMPLIFIED INSTALLATION WITH A HIGH-PERFORMANCE SYSTEM

QUAD® MAX is the first line of defense against air and moisture entering the home. It won't yellow, crack or collect dirt. It can be perfectly color matched to any JELD-WEN® window or door.

QUAD® FOAM stops air and moisture infiltration. The foam is closed-cell and flexible but will not crack. It has an insulation value of R5 per inch and an application temperature as low as 14°F.

Flashing tape is a high-performance membrane designed to help stop the passage of bulk water and air flow. The membrane is also vapor non-permeable and is fully compatible with the OSI® QUAD® Installation System.

Quad® Flash is a gun-grade waterproofing sealant compound designed for use in rough openings of structural walls. It allows for same-day installation of windows, doors and other wall assembly components and offers a strong bond to primary window, door and wall sheathing materials.

The OSI® QUAD®

Installation System protects
against air and water infiltration
through the rough openings
in new construction and
replacement applications and
is backed by a 15-year limited
warranty* when installed by an
OSI-certified trained installer.



Drip cap

• Square, plumb, level, winding, bow and sag requirements

- Shimming
- Proper fastening
- Side and back dams to sill pan and down turn leg when applicable
- Interior air and water seal
- Proper operation

Complete OSI® QUAD®
Installation System can
be ordered through
IELD-WEN QuickQuote®

*Limited Warranty exclusions and limitations apply. Visit ositough.com for more information.